D3 Expansion Module

High resolution, easy-to-use expansion module



D3 Expansion Module



Key Features

- · 18 highly configurable self-labeling multicolor LED keys
- · High-resolution black & white display with backlight
- · Daisy-chain up to 3 modules
- Plug and play
- \cdot Power supplied by phone via USB port

The D3 Expansion Module provides an elegant way to increase the available function keys on D3xx telephones, allowing users to manage a large number of extensions and calls.

Flexibly Programmable Keys

The D3 expansion module features 18 multicolor LED keys which can be programmed with all functions available on Snom phones like line, speed dial, busy lamp field, presence indication, and many more.

The call or presence status of your contacts is presented by the D3's multicolored LED keys at any given time. The high-resolution display provides a perfect visual interface which can be easily configured and labeled via the phone's web interface or directly on the phone itself.

Ease Of Use

Using the D3 could not be easier: simply connect the USB cable and it's ready to use. Even power is supplied by the host phone⁽¹⁾.

Three D3 expansion modules can be daisy-chained to add up to 54 function keys to your phone. The USB port on the last D3 in the chain can be used to connect other peripheral USB devices like USB headsets or WiFi sticks to the host phone. The D3 is the perfect addition to any D3-series desk phone with a USB port.

SN()M

Benefits

- \cdot High-resolution graphical display with backlight
- \cdot 18 freely programmable multicolor LED function keys
- · Daisy chainable
- · Fully configurable via host phone
- \cdot Powered by host phone^{\scriptscriptstyle (1)}

Specification

Installation

- \cdot Plug and Play
- \cdot Completely configurable via host phone

Features

- · Dimensions (approx.): 140 x 170 x 80mm (LxWxH)
- · Weight (approx.): 300g
- · Input voltage: 5V DC (SELV)
- \cdot Power supply: USB or 5V DC power adapter $^{\scriptscriptstyle (2)}$
- · USB 2.0 port, type A
- · USB 2.0 port, type B
- · Environmental conditions:
 - · Ambient temperature: 0°C to 35°C (32°F to 95°F)
 - Non-operation: -10°C to 45°C (14°F to 113°F)
 - Humidity: 5% to 95% (non-condensing)
- · Included in delivery:
 - · Base unit
 - · USB cable type A/type B
 - · Quick Start Guide
- \cdot Color: Black-blue
- · Warranty: 2 Years
- · Part Number: 00004327

Type Approval

- · CE Mark
- · FCC Class B
- · Safety IEC 60950, CB

Compatible with

- · D315 (Snom PN 00004258)
- · D345 (Snom PN 00004260)
- · D375 (Snom PN 00004141)
- ⁽¹⁾When two or three modules are used with one phone, a separate power supply needs to be connected to the second module.
- ⁽²⁾ Optional accessory (see below for part numbers)

Part Numbers for Optional Accessories

- 00004325Power Adapter Snom A6 / EU clip00004326Power Adapter Snom A6 / US clip00001168UK clip for Snom A6
- 00001167 AUS clip for Snom A6

Version 1.0.2 / en / 04 · 2017 Copyright 2017 Snom Technology GmbH. All rights reserved.

Snom is a registered trademark of Snom Technology GmbH and its affiliates in the European Union, USA, Japan, China and certain other countries and regions. Unless specified otherwise, all trademarks, in particular product names, are legally protected trademarks of Snom Technology GmbH. Other mentioned trademarks or registered trademarks are the property of their respective manufacturers or owners. Product specifications are subject to change without notice. We do not accept liability for printing errors and mistakes. snom.com